

DYNAMITE 760

- Excellent tack, strong bond
- Extremely resistant to high humidity
- Needs no primer
- Great for pasting machines

Dynamite™ 760 Vinyl Over Vinyl Wallcovering Adhesive is specially designed for installing vinyl or foil wallcoverings over existing vinyl wallcoverings and other difficult surfaces. Dynamite 760 is also used for installing all types of borders over existing wallcoverings and other difficult surfaces. This product cleans up with water while wet.

- Bonds vinyl and foil wallcoverings and borders to existing vinyls, foils and difficult surfaces such as glass, mirrors, wood, metal and plastic without the need for priming.
- Can be used for applying borders and wallcoverings over archways, outside corners, overlay areas or for repairing curled seams.
- Great for pasting machines

DO NOT USE OVER SILICONE- OR WAX-COATED SURFACES. NOT RECOMMENDED FOR USE WITH HIGH-SHRINKAGE WALLCOVERINGS (many grass-cloths, strings and untreated fabrics) OVER VINYL WALLCOVERINGS.

PREPARATION: Surface must be clean and free of oil, dust, dirt, grease, mildew, and other foreign matter. For best results, use Dynamite All-Purpose Cleaner to prepare walls. A diluted household bleach solution also works well to clean walls. Repair or fill cracks in wall with Dynamite Non-Shrink Spackling. No priming is required with this Dynamite adhesive product.

APPLICATION: Mix well before using to ensure even consistency. Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller, stiff brush or pasting machine. Allow proper booking time according to manufacturer's instructions. (NOTE: When hanging pre-pasted borders, dampen back of border with wet sponge. Wait 2 minutes, then apply Vinyl Over Vinyl in a thin, even coat to the back of the border. This prevents over-absorption of the paste. Strip should be booked for 5 minutes prior to hanging.) IMMEDIATELY remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge.
HANG WALLCOVERING ACCORDING TO MANUFACTURER'S INSTRUCTIONS

COVERAGE: One gallon will hang up to 8 single rolls (280 sq. ft.). Coverage rates can vary depending on condition of the substrate, priming and sizing, weather conditions and method of application.

©2006 Gardner-Gibson, Inc.
Manufactured by:
Gardner-Gibson, Inc.
P.O. Box 5449
Tampa, FL 33675

See MSDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight per Gallon	8.9 lbs.
Color	Off White
Odor	Mild
Consistency	Smooth Paste
Viscosity	30,000-35,000
pH	6.8
Solvent	Water
Freeze-Thaw Stability	Yes
Open Time	25 minutes
% Solids	35% +/- 2%
Recommended Storage Temperature	40 F to 100 F.
Recommended Application Range	45 F to 100 F.
Flash Point	None
Shelf Life	12 months
Resistance to Mold & Mildew	Excellent

Approx. Shipping Weights: (Note: All approx. weights include container.)

1 quart (1.0L)	2.5 lbs.
1 gallon (3.8L)	9.4 lbs.
5 gallons (18.9L)	46.0 lbs

CAUTION! DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of warm water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. When transporting product, be sure lid is tight and product is kept upright and secure. Do not store/warehouse product below 32°F.

WARNING: This product contains a chemical known to the State of California to cause cancer. Keep container closed when not in use.

VOC: < 31.0 g/L of material

INGREDIENTS: (>1% of total weight):
COPOLYMER (25067-01-0), DEXTRIN (9004-53-9), ETHYLENE GLYCOL (107-21-1), WATER (7732-18-5)

QUALITY PROMISE: Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.